Buena Vista

Crystal Pacific, Series 9000

Sliding Doors

U-Value SHGC

OITC

Custom & Standard Sizes

Outside View. Frame: 5-1/4-in. Threshold: 1-11/16-in. Glass: 1-in.



2PD (2-Panel)

<u>3PD (3-Panel)</u> XOO, OOX, OXOL, OXOR

4PD (4-Panel)*		
OXXOL, OXXOR		

Glass

ENERGY - LE3/Ar......1/8-1/8.......0.29........0.22

ACOUSTIC<u>1/8-3/16</u> 3226

*Special vent size available.

1/8-3/16 0.29 0.22 STC

3/16-1/4 34 27

<u>Limitations</u>	Min (in.)	Max (in.)	PG (DP)
2PD	60 x 70	96 x 96	25
2PD	60 x 70	120 x 82	20
3PD	90 x 70	144 x 92	
4PD Retro	120 x 70	187.5 x 92	
4PD Nail	120 x 70	189 x 92	
4PD Block	120 x 70	192 x 92	

Features

QUALITY VINYL

15-point inspection program for quality assurance.

EFFICIENT DESIGN

Multichambered frame, interlocking sash, and weather strips provide strength and efficiency.

ENERGY-EFFICIENT GLASS

Tempered insulated glass units (double pane) with a highperformance stainless steel spacer system.

USER-FRIENDLY SASH

Durable dual-point locking, sturdy crescent handle, and easy sliding with end-adjustable dual rollers on a monorail track.


BETTER SCREENS

Quality aluminum screen door with a wide weather strip.


Frames

NAIL

Nail Fin: 1-1/4-in. Setback: 1-in. Stucco Key: 3/16-in.




BLOCK No fin.



RETRO

Dual-Wall Flush Fin: 2-1/16-in. 3-sides (block sill) or 4-sides (retro sill, 4th z-bar shown).



Options

EXTERIOR COLORS

Performance

A color is applied to the exterior, the interior remains white.

PERFORMANCE GLASS

Increase energy efficiency with LowE3 and Argon (LE3/Ar).

DISSIMILAR GLASS

Reduce sound transmission with 1/8-3/16 insulated glass.

STAINLESS STEEL


Upgrade your dual-point locking system and dual rollers.

BETWEEN-THE-GLASS GRIDS

Divide lites with style, choose 5/8 flat or 1-inch sculptured.

SPECIALTY GLASS

Add privacy and beauty with semi-opaque glass options.



WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov.