

### Types

Choose flat or sculptured aluminum grids.



**5/8" Flat**



**1" Sculptured**



Grid measurements based on larger glass unit.

Drawing required for special grid patterns.

Adding grids may improve energy rating.

### Colonial Pattern

Lite sizes for the colonial pattern are based on 12 inches for windows and 15 inches for doors. Depending on the size of the window or door, the lite size can be more or less within a few inches.

The default number of lites will be used, unless a drawing with the preferred number of lites is provided. Keep in mind, more lites results in more grids hindering the view.

#### \*COLONIAL LITES & GRIDS

4W3H = 4-Wide, 3-High (Lites Per Window or Door)

1V2H = 1-Vertical, 2-Horizontal (Grid Bars Per Panel or Glass Unit)

### Marginal & Queen Anne Patterns\*\*

Grid perimeter is 4 inches from the edge of the glass unit to the center of the grid bar.

An extra charge may be applied if window height is less than 14 inches and or Queen Anne window width is less than 28 inches.

\*\*Not available with swing doors.


\*\*Not recommended with active panels.

### Valance Pattern

Default Valance pattern height is 10 inches from the edge of the glass unit to the bottom of the grid bar. The default will change to the middle of the glass unit if the height of the glass unit is less than 20 inches.

### Patterns


Select a grid pattern.



Lites/Window  
4W3H\*


Grids/Panel  
1V2H\*

**Colonial (Traditional)**



4 in.

**Marginal (6-lite Perimeter)**



4 in.

**Queen Anne (9-lite Perimeter)**



↓ 10 in.

**Valance (Top Row)**



**Starburst (3-spoke)**