

		STRUCTURAL			ENERGY				ACOUSTIC						Reinforcement
		MIN Minimum Size	MAX Maximum Size	PG DP	LowE3/Argon Double Pane	U-Value Insulation		SHGC Heat Gain		VT Visible Light		STC Sound	OITC Transfer	MATERIALS	
Vinyl Windows & Doors		W x H	W x H	Rating	Thickness, in./mm	N	G	N	G	N	G	Higher, Better			
Vista Windows	2SSL: XO, OX	24 x 12	72 x 72	LC25	3/32-3/32 2-2	0.30	0.31	0.22	0.20	0.53	0.47	27	22	STEEL	
			71 x 59.25	LC35	3/32-1/8 2-3	0.30	0.30	0.22	0.20	0.53	0.47	27	24	F.G	
			84 x 60	LC25	1/8-1/8 3-3	0.30	0.30	0.22	0.20	0.52	0.47	26	22	F.G	
			72.25 x 72.06	R20	1/8-3/16 3-5	0.30	0.31	0.22	0.20	0.52	0.46	30	26	F.G	
			73 x 73	R15	3/16-3/16 5-5	0.31	0.34	0.23	0.20	0.51	0.46	27	24	F.F	
	3SSL: XO, XO, XO, XO, XO, XO*	65 x 12 *48 x 12	72 x 60	R20										F.F	
			96.5 x 60	R20										F.F	
			120.5 x 60	R15										F.F	
	SH: O/X	12 x 24	48 x 84	LC30	3/32-3/32 2-2	0.30	0.30	0.22	0.20	0.53	0.47	29	26	STEEL	
			47.4 x 82.85	LC30	3/32-1/8 2-3	0.29	0.29	0.22	0.20	0.53	0.47	30	24	F.G	
			44 x 75	LC35	1/8-1/8 3-3	0.30	0.30	0.22	0.20	0.52	0.47	29	25	F.G	
			40.5 x 72.5	R30	1/8-3/16 3-5	0.30	0.31	0.22	0.20	0.52	0.46	34	29	F.F	
			88 x 75	LC35	3/16-3/16 5-5	0.31	0.33	0.23	0.20	0.53	0.53	33	28	F.G	
	SH3: O/X3	12 x 36	40.5 x 84.5											F.G	
														F.G	
														F.G	
														F.F	
Vista Plus Windows	PW: O	12 x 12	72 x 71	LC25	3/32-3/32 2-2	0.26	0.27	0.24	0.22	0.59	0.53	27	24		
			72.37 x 72.37	CW40	3/32-1/8 2-3	0.26	0.26	0.24	0.22	0.58	0.52	33	27		
	Geo, Trapezoid	12 x 7	72 x 72		1/8-1/8 3-3	0.26	0.26	0.24	0.22	0.58	0.52	30	25		
	Arch, Half Circle	30 x 15	76 x 42		1/8-3/16 3-5	0.26	0.28	0.24	0.22	0.57	0.52	35	29		
	Arch, Eyebrow	21 x 11.75	103 x 48		3/16-3/16 5-5	0.27	0.30	0.25	0.23	0.57	0.51	33	28		
	(May Require Leg)	Radius: 15	Length: 120												
	2SSL: XO, OX	27 x 15.5	72 x 72	LC30	1/8-1/8 3-3	0.30	0.30	0.21	0.19	0.50	0.44	—	—	F.G	
			84 x 60	LC25	1/8-3/16 3-5	0.30	0.30	0.21	0.19	0.49	0.44	32	25	F.G	
			72 x 102	LC25	3/16-3/16 5-5	0.29	0.29	0.21	0.19	0.49	0.43	—	—	F.G	
	3SSL: XO, XO, XO, XO, XO, XO*	53 x 15.5 *38 x 15.5	120 x 60		1/4-1/4 6-6	0.29	0.29	0.21	0.19	0.48	0.43			F.G	
	SH: O/X	15.5 x 27	47 x 84	LC30	1/8-1/8 3-3	0.30	0.30	0.21	0.19	0.50	0.44	—	—	F.G	
			47 x 96		1/8-3/16 3-5	0.30	0.30	0.21	0.19	0.49	0.44	32	26	F.G	
					3/16-3/16 5-5	0.29	0.29	0.21	0.19	0.49	0.43	—	—		
	SH3: O/X3	15.5 x 41			1/4-1/4 6-6	0.29	0.29	0.21	0.19	0.48	0.43	—	—		
	PW: O	15.5 x 15.5	72 x 72	CW30	1/8-1/8 3-3	0.28	0.28	0.22	0.20	0.52	0.47	28	22	F.G	
					1/8-3/16 3-5	0.27	0.27	0.22	0.20	0.52	0.46	33	25		
					3/16-3/16 5-5	0.27	0.27	0.22	0.20	0.51	0.46	—	—		
* No Label	CA: CL, CR	15 x 17.5	32 x 60	CW40	1/8-1/8 3-3	0.27	0.27	0.19	0.17	0.43	0.39	31	24		
			36 x 72	LC45	1/8-3/16 3-5	0.26	0.26	0.18	0.17	0.42	0.38	35	27		
			72 x 84	LC45	3/16-3/16 5-5	0.26	0.26	0.18	0.17	0.42	0.38	—	—		
			72 x 72	LC45	1/4-1/4 6-6	0.26	0.26	0.19	0.17	0.41	0.37				
			90 x 84	LC45											
	AW: A	13 x 12	60 x 36 (*42)	LC45											
	CF: O	13 x 12	72 x 72												
Buena Vista Sliding Doors	2PD: XO, OX	60 x 70	96 x 96	LC25	1/8-1/8 3-3	0.29	0.29	0.22	0.20	0.53	0.46	28	21		
			120 x 82	LC20	1/8-3/16 3-5	0.29	0.29	0.22	0.20	0.52	0.46	32	26		
			72 x 84	LC30	3/16-3/16 5-5	0.28	0.28	0.22	0.20	0.52	0.45				
	3PD: XO, OX	90 x 70	144 x 92		3/16-1/4 5-6	0.28	0.28	0.22	0.20	0.51	0.45	34	27		
	4PD: OXO Retro	116 x 70	187.5 x 92		1/4-1/4 6-6	0.28	0.28	0.22	0.20	0.51	0.45				
	4PD: OXO Nail		189 x 92												
Valencia Windows	2DSL: XX	24 x 15.5	63 x 44	R60	1/8-1/8 3-3	0.28	0.28	0.21	0.19	0.50	0.49			STEEL	
					3/16-3/16 5-5	0.28	0.28	0.21	0.19	0.49	0.43				
	2SSL: XO, OX	24 x 15	63 x 44	R55	1/8-1/8 3-3	0.29	0.29	0.21	0.19	0.50	0.45			STEEL	
					3/16-3/16 5-5	0.28	0.28	0.21	0.19	0.50	0.44				
Valencia Inswing, Outswing Doors	DHT: X/X	15.5 x 20.5	44 x 63	R60	1/8-1/8 3-3	0.28	0.28	0.21	0.19	0.48	0.43			STEEL	
					3/16-3/16 5-5	0.28	0.28	0.21	0.19	0.48	0.42				
	SHT: O/X	15 x 20.5	44 x 75	LC40	1/8-1/8 3-3	0.28	0.28	0.21	0.19	0.50	0.44			STEEL	
					3/16-3/16 5-5	0.28	0.28	0.21	0.19	0.49	0.43				
Valencia Inswing, Outswing Doors	PW: O	12 x 12	72 x 72	LC45	1/8-1/8 3-3	0.28	0.28	0.23	0.21	0.53	0.48			NONE	
					3/16-3/16 5-5	0.27	0.27	0.23	0.20	0.52	0.47				
	French: XXL, XXR With 1-Sidelite**	48 x 75 66 x 75 84 x 75	72 x 96	Up to 40	1/8-1/8 3-3	0.31	0.31	0.17	0.15	0.37	0.32				
			96 x 96		1/8-3/16 3-5	0.31	0.31	0.17	0.15	0.37	0.32				
			120 x 96		3/16-3/16 5-5	0.31	0.31	0.17	0.15	0.37	0.31				
Valencia Inswing, Outswing Doors	Hinged: XL, XR With 1-Sidelite**	24 x 75 42 x 75 60 x 75	36 x 83		3/16-1/4 5-6	0.30	0.30	0.17	0.15	0.36	0.31				
			60 x 83		1/4-1/4 6-6	0.30	0.30	0.17	0.15	0.36	0.31				
			84 x 83												
	**Fixed, Hinged	18 x 75	24 x 96												

Combination Windows (Stack/Mull): Not to exceed 60 sq. ft. overall; Max Width 144 in. (12 ft.); Max Height 108 in. (9 ft.)

PG Performance Grade (Design Pressure) **STC** Sound Transmission Class **OITC** Outdoor-Indoor Transmission Class

U-Value (U-Factor) Insulation value of windows **SHGC** Solar Heat Gain Coefficient **VT** (VLT) Visible Transmittance **N** No Grids **G** Grids

Title 24 (California): Prescriptive Max. U-Value 0.30, SHGC 0.23 **ENERGY STAR®** (South Central): Max. U-Value 0.30, SHGC 0.25

Other limitations may apply.

Subject to change without notice.

REF-LP-070125 © CPWDS.com